



## TECHNICAL DATA SHEET

### SUPER LUBE® MULTI-PURPOSE SYNTHETIC OIL WITH SYNCOLON® (PTFE) NON-AEROSOL PUMP

July 2017

#### PRODUCT DESCRIPTION:

Super Lube® Multi-Purpose Synthetic Oil with Syncolon® (PTFE) Non-Aerosol pump was developed because of environmental concerns. Many industrial facilities do not allow the use of aerosol products. This product addresses these needs.

Super Lube® Multi-Purpose Synthetic Oil is a premium synthetic oil with suspended Syncolon® (PTFE) particles that is used as a general-purpose lubricant for industrial machinery and equipment. Provides protection against friction, wear, rust and corrosion. Machinery lasts longer, downtime is reduced, and productivity is increased.

Super Lube® Multi-Purpose Synthetic Oil with Syncolon® (PTFE) is safe to use on metal, plastic, wood, leather, painted surfaces and most rubbers.

Super Lube® Multi-Purpose Synthetic Oil with Syncolon® (PTFE) is a NSF registered Food Grade Lubricant, rated H1 for incidental food contact. Meets former USDA (H1) guidelines.



#### FEATURES:

- ❖ Ozone friendly
- ❖ Will not attract dust
- ❖ No CFCs
- ❖ Fortified with Syncolon® (PTFE)
- ❖ Reduces friction and wear
- ❖ Displaces moisture
- ❖ Prevents rust and corrosion
- ❖ Dielectric
- ❖ Kosher certified
- ❖ NSF Registered H1, # 136742
- ❖ Environmentally friendly

#### TYPICAL APPLICATIONS:

- ❖ Linkages, hinges and locks
- ❖ Prop shafts/trim tabs
- ❖ Canvas snaps and zippers
- ❖ Windows, garage doors, appliances
- ❖ Winches and sail tracks
- ❖ Sewing machines, lawn mowers
- ❖ Trailer rollers and casters
- ❖ Shop tools, cutting oils
- ❖ Campers/trailers, mopeds/go carts
- ❖ Motorcycles, snow mobiles, jet skis, ski bindings
- ❖ Fishing and hunting gear, firearms

**TECHNICAL DATA SHEET****SUPER LUBE® MULTI-PURPOSE SYNTHETIC OIL  
WITH SYNCOLON® (PTFE) NON-AEROSOL PUMP**

July 2017

**PACKAGE SIZES:**

Part No.	Description
51600	1 Quart Bottle with Trigger Sprayer

**PROPERTIES:**

Test	Test Method	Rating
Color:		Translucent clear
Temperature range		-45°F to 450°F (-43°C to 232°C)
ISO Viscosity grade	ASTM D445	100
Specific gravity	ASTM D1298	0.845 – 0.855

**DIRECTIONS:**

- Wipe areas to be treated.
- Apply enough oil to coat all areas of contact.
- Re-apply as needed.

**SHELF LIFE / WARRANTY:**

Super Lube® products have a five (5) year recommended shelf life when stored in the original container and in reasonable ambient conditions. The warranty period is twenty-four (24) months from the date of purchase. For complete information visit [www.super-lube.com/what-is-the-shelf-life-ezp-320.html](http://www.super-lube.com/what-is-the-shelf-life-ezp-320.html).



See Safety Data Sheet (SDS)  
for further details regarding  
safe use of this product.



Made in USA

The information provided in this Technical Data Sheet, including the recommendations for use and application of the product are based on our knowledge and experience of the product as of the date of this data sheet. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Synco Chemical Corporation is, therefore not liable for the suitability of our product for the production processes and conditions in respect for which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

All Super Lube® and Syncolon® trademarks in this document are trademarks of Synco Chemical Corporation.