



GREAT STUFF PRO™ WINDOW & DOOR INSULATING FOAM SEALANT AN AIRTIGHT CASE



Close the Gap

Seal out energy loss and help improve comfort by closing the gap between the framework and rough openings around windows and doors with GREAT STUFF PRO™ Window & Door Insulating Foam Sealant.⁽¹⁾

The low pressure-build formulation of GREAT STUFF PRO™ Window & Door Insulating Foam Sealant forms a durable, airtight and water-resistant seal between a window or door frame and its rough opening.

GREAT STUFF PRO™ Window & Door Insulating Foam Sealant is available in a 20 oz gun-applied version. The gun formulation can be used with the PRO Series Foam Dispensing Guns and is designed specifically for the professional contractor.

GREAT STUFF PRO™ Window & Door Insulating Foam Sealant can be used to seal around windows and doors and their rough openings in:

- Commercial Construction
- Residential Construction

Features and Benefits At a Glance

- Meets ASTM E2112 standards
- Low pressure-build formulation at 0.13 psi; 0.90 kPa (average) (gun foam) per AAMA 812-04
- When properly installed is proven not to bow or distort frame
- Expands to take the shape of gaps, creating a long-lasting, airtight and water-resistant seal
- Helps to maximize energy efficiency
- Bonds to vinyl, metal, wood and composite surfaces
- Repels and deflects water
- Tack-free in 3-10 minutes, Trims in 60 minutes¹
- Fully cured in 8 hours
- UL classified
- One 20 oz. can (gun-applied) foams 16-18 average sized residential windows²
- When cured, remains soft and flexible. Cured foam can be stuffed back into the gap without trimming.
- Clean up of uncured foam is easy with GREAT STUFF PRO™ Gun Cleaner

Grainger Part Number	Product Name
48WK22	GREAT STUFF PRO™ Pestblock 20 OZ
48WK21	GREAT STUFF PRO™ Window & Door 20 OZ
48WK20	GREAT STUFF PRO™ Gaps & Cracks 24 OZ
48WK24	GREAT STUFF PRO™ 14 Dispensing Gun
48WK23	GREAT STUFF PRO™ Gun Cleaner 12 OZ



Windows and their rough openings

¹ Consult label and (Material) Safety Data Sheet carefully before use.

² 70 ±5 °F and 50 ±5 %RH, 1 inch bead diameter, 6 inch length. Cure rate is dependent on temperature, humidity, and size of foam bead.

³Based on average-sized windows 36" x 60", 3/8" wide gap, and 1" deep.

With GREAT STUFF PRO™ Window & Door Insulating Foam Sealant, you can achieve better window or door installation. GREAT STUFF PRO™ Window & Door helps to prevent drafts, repels water and more, resulting in higher quality installation, improved building comfort and greater customer satisfaction.



Doors and their rough openings

PRO Series Foam Dispensing Gun

GREAT STUFF PRO™ 14 Dispensing Gun

- Precision application
- High yield
- No drip dispensing
- 30 day restartability



Formulated for the Pros

Count on the GREAT STUFF PRO™ family of products to help you handle the toughest jobs.

- GREAT STUFF PRO™ Gaps & Cracks Insulating Foam Sealant
- GREAT STUFF PRO™ Window & Door Insulating Foam Sealant
- GREAT STUFF PRO™ Pestblock Insulating Foam Sealant
- GREAT STUFF PRO™ Gun Cleaner



For more information contact your Grainger representative or visit Grainger.com

GRAINGER
FOR THE ONES WHO GET IT DONE

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

Dow Polyurethane Foam Insulation and Sealants

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult (Material) Safety Data Sheet ((M)SDS), call Dow at 1-866-583-BLUE (2583) or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S or 1-519-339-3711 in Canada. When air sealing buildings, ensure that combustion appliances, such as furnaces, water heaters, wood burning stoves, gas stoves and gas dryers are properly vented to the outside. See website: <http://www.epa.gov/iaq/homes/hip-ventilation.html>. In Canada visit <http://archive.nrc-cnrc.gc.ca/eng/ibp/irc/bsi/83-house-ventilation.html>

GREAT STUFF PRO™ Insulating Foam Sealant and adhesive products contain isocyanate and a flammable blowing agent. Read all instructions and (Material) Safety Data Sheet ((M)SDS), carefully before use. Eliminate all sources of ignition before use. Cover all skin. Wear long sleeves, gloves, and safety glasses or goggles. Not for use in aviation, or food/beverage contact, or as structural support in marine applications. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure. Not to be used for filling closed cavities or voids such as behind walls and under tub surrounds; this improper use of the product could result in the accumulation of flammable vapors and/or uncured material. Failure to follow the warnings and instructions provided with the product, and/or all applicable rules and regulations, can result in injury or death.

GREAT STUFF PRO™ Gun Cleaner is flammable and contains acetone and propane. Read all instructions and (M)SDS carefully before use. Eliminate all sources of ignition before use. Cover all skin. Wear gloves, and goggles or safety glasses. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.