

EcoClean[®] 60 100% Cotton Nonwoven Cleanroom Wiper

EcoClean[®] is an environmentally friendly wipe that has been designed for ISO Class 5 (Class 100) and above cleanroom applications. EcoClean[®] is 100% biodegradable and renewable. It is made from 100% natural fiber that contains no binders or additives, and it is manufactured by a proprietary process for low fiber release and high strength. EcoClean®60 can be used in critical pharmaceutical, medical device, and Product Information ISO Class 5 – 8 Cleanroom Class 100 – 100,000 EU Grade B/C/D USP <797>



Berkshire is committed to lessen the environment impact of its manufacturing process and products through its **Green Scope Program**

semiconductor applications where absorbency and softness are required.

	and the second second second	and the second s					「「「「「「」」」」」」」」」」」」」」」」」」」」」」」」」」」」」」」		あるとうとなっていたいでものであったので	a state of the second second	「「「「「「「「」」」」」」」」」」」」」」」」」」」」」」」」」」」」」	the second s		and a state of the	and the second se	and the second se	

- Other Green Scope products: • Sunsorb[®] 300
- Lensx[®] 90
- Labx[®] 170
- Twillx[®] 1622
- EcoClean[®] 35
- EcoBond®

Key Attributes

- 100% nonwoven cotton
- Manufactured by a proprietary process for low fiber release and high strength
- No binders or other additives
- Low ionic contamination

Benefits

- Excellent strength
- Heat resistant
- Highly absorbent and durable
- Extremely soft
- Resists build up of static charge

Environmental

- Light weight, high absorbency design reduces landfill waste impact when compared to more traditional heavier weight products
- EcoClean[®] is 100% biodegradable and renewable

Applications

- Cleaning high temperature production equipment and diffusion furnaces
- Absorbent, low linting work surface material
- Removing aqueous and solvent spills
- Critical industrial applications where absorbency and softness are critical
- · Cleaning of support/less critical areas and manufacturing processes in regulated environments
- Wiping of optics and other sensitive surfaces
- Steam autoclavable for aseptic applications
- Compatible with ISO Class 5 (Class 100) cleanroom applications and above
- EC Regulation 1935 (2004) Food contact compliant
- FDA 21 CFR Food contact compliant



Technical data:

Attribute		Units	Value	Test Method				
Basis Weight		g/m ²	59.6	TAPPI T-410				
Caliper		μm	270	TAPPI T-411				
Fibers	≥100µm	fibers/cm ²	39	IEST-RP.CC004.3, Sec 6.1.3 / Sec 6.2.2				
Particles	≥0.5µm	x10 ³ /cm ²	35	IEST-RP.CC004.3, Sec 6.1.3 / Sec 6.2.1				
Sorbency	Capacity	mL/m ²	385	IEST-RP.CC004.3, Sec 8.1 modified / Sec 8.2 modified				
	Efficiency	mL/g	6.5					
	Rate	seconds	1					
Non-Volatile Residue	DI Water	g/m ²	0.023	IEST-RP.CC004.3, Sec 7.1.2				
	IPA	g/m ²	0.016					
Ions	Na ⁺	ppm	110	IEST-RP.CC004.3, Sec 7.2.2				
	K+	ppm	0.59					
	Ca++	ppm	1.3					
	Mg ⁺⁺	ppm	0.50					
	CI-	ppm	20					

Notes:

- Technical data represented in this table are typical values at the time of publication. These should not be used as product specifications.
- Due to differences in test methods applied and equipment utilized by different wiper manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions
 Third parts testing are be parformed upper result.
- Third party testing can be performed upon request

Order Information:

Product	Number	Size	Shts/pk	Pks/cs
EcoClean [®] 60	ECW60.0909.20	9x9" (23x23cm)	300	20
EcoClean [®] 60	ECW60.1212.20	12x12" (30x30cm)	150	20





- -