

HAZARD WARNING TAPE

*Specialists in
Safety
Identification
Products*

APPLICATION:

Designed expressly for safety marking applications in industrial plants, commercial buildings, institutions and recreational facilities.

Tape fulfills all OSHA requirements. Used to mark obstructions, low hanging objects, pillars, handrails, passageways, aisles and any potentially hazardous areas or objects.

FEATURES / BENEFITS:

- Engineered to hold up under the heaviest most abusive traffic and wear . . . longer than paint!
- Clear embossed protective PVC laminated to a printed PVC layer to give a total backing thickness of 7.5 mils. Prevents fading and scuffing; provides super abrasion resistance.
- Can be applied quickly and easily; requires minor surface preparation, with no time consuming scraping and cleaning necessary.
- No downtime required for drying after installation.
- Maintenance-free. Original color brilliance is continually renewed by simple wet mopping/washing.
- Conforms with OSHA requirements.

COLORS:

Yellow/Black, White/Red, White/Green, White/Black

TECHNICAL DATA:

Backing Material:	Plasticized PVC
Adhesive:	Rubber Based Adhesive
Total Tape Thickness:	7.5 mil; 0.19 mm; Laminated with BOPP film.
Tensile Strength (N/cm):	32N/cm
Elongatin at Break (%):	200%
Peel Adhesion (N/cm):	1.2N/cm
Unwinding force (N/cm):	2.8N/cm
Temperature Resistance (°C):	-10°C -- +80°C
Shelf Life (month)	12 months

Harris West

5181 Argosy Avenue
Huntington Beach, CA 92649

Phone:
(714) 898-8048
(800) 222-6866

Fax:
(714) 898-7108
(800) 228-1274

Harris East

181 Conant Drive
Pawtucket, RI 02860

Phone:
(401) 727-3160
(800) 443-2821

Fax:
(401) 727-3162

Note: The above are typical values and should not be used in writing specifications.