PIG® 5-Gallon Latching Pail Lid

#DRM1200 - For 5-gal. Plastic & Steel Pails • Hinged w/ One Hand Latch



Use our latching lid with fast-latch ring on your steel or poly 5-gallon pails -- it's the first to fit them both! Only from New Pig.

- Use this versatile lid on a steel pail one week and a poly pail the next - our PIG-exclusive design fits both!
- Reinforced hinge, latching mechanism and EVA gasket provide a tight seal to help keep pail contents pure; also help reduce vapor emissions
- Single latching hasp easily opens and closes; padlockable to increase security
- Powdercoated steel construction is built to stand up to harsh treatment
- Fast-latch ring makes installation easy on steel or poly openhead 5-gallon pails with a 11.25" inside diameter; no clumsy nut-and-bolt ring
- Lid stop on hinge keeps lid upright when open

DRM1200 Specifications

Style: Hinged w/ One Hand Latch
Use With: 5-gal. Plastic & Steel Pails

Padlockable: Yes

Sold as: 1 per box

New Pig Patent: Patent 8,480,139

per Pallet: 40

Composition: Lid: Steel

Gasket: 2.375" wide EVA (Ethylene-Vinyl

Acetate)

UNSPSC: 24112112

Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

29 CFR 1910.134)(a)(1) - Engineering controls should be used as a first step in controlling harmful dusts, fogs, fumes, mists, gases, smokes, sprays, or vapors in the workplace.

29 CFR 1910.106(e)(2)(i) - Flammable liquids need to be stored in closed containers that are sealed by a "lid or other device" that does not allow liquids or vapors to escape.

40 CFR 261.4 - Helps you comply with 40 CFR 261.4 requiring excluded solvent contaminated wipes to be accumulated and stored in closed containers while they are managed onsite.

29 CFR 1910.22(a) - All places of employment "shall be kept clean and dry and in a sanitary condition" and floors shall be kept clean and dry.

40 CFR 264.1086(c)(1)(ii) - Level one containers must have closure devices that, "form a continuous barrier over the container openings." When these closure devices are in place, there can be, "no visible holes, gaps or other open spaces into the interior of the container."

40 CFR 262.34(c)(1) - Satellite Accumulation Areas allow generators of hazardous waste to accumulate as much as 55 gallons of hazardous waste or one quart of acutely hazardous waste in containers at or near the point of generation. The container must be kept closed when not in use, must be under the control of the operator generating the waste and must be properly labeled.

Technical Documents:

(Available at newpig.com)
Product Data Sheet (PDS)
Chemical Compatibility (CCG)





